169.00 EUR
incl. 19% VAT, plus shipping

Support: Specifications [EN]

- INTEL® Pineview-M + NM10 Chipset
- Support INTEL®ATOM N455 Single-Core (1.66GHz) CPU
- Support 3Gb/s SATA■ with RAID 0, 1 and JBOD
- Supports 2 * Gigabit LAN

- Integrated VIA VT1705 HD Audio Code with 6-Channel
- Support Watch dog Technology
- Compliance with ERP standard
- Mini-ITX Form Factor(170mm x 170mm)
- Support Daughter board Expansion

CPU	INTEL ®Atom Single-Core N455 CPU(45nm,FSB 667MHz,1.66GHz,512KB L2 Cache)
Chipset	INTEL®Atom N455 + NM10 chipset Build-in INTEL®GMA 3150 Graphics Core (DVMT Max. 384MB)
Memory	2 * SO-DIMM Sockets for un-buffered Single Channel DDR3 800 SDRAM up to 2 GB
Expansion Slots	1 * PCI slot 1 * Mini PCI-E socket
Storage	4 * Serial ATA2 3Gb/s connectors support RAID 0, 1, JBOD 1 * IDE connector
Audio	VIA VT1705 HD Audio Code with 6-Channel
Ethernet LAN	Realtek RTL8111E PCI-E Gigabit Ethernet LAN
USB	Embedded 7 * USB 2.0/1.1
Special Features	Support ACPI S3 Support CPU Smart FAN & DC FAN
LVDS	Onboard 18-bit Single Channel LVDS connector
Rear Panel I / O	4 * USB 2.0/1.1 ports 1 * PS/2 KB/MS connector 2 * RJ-45 port 1 * Audio I/O port (Line-in, MIC and Line-out) 1 * VGA port 1 * COM port
Internal I / O	3 * USB 2.0 ports CPU / Chassis Fan connectors 1 * 24-pin ATX Power connector 1 * COM header (COM2 for RS-232/422/485) 1 * AUDIO_IN header 1 * Parallel header 1 * GPIO header
BIOS	Award 8MB DIP-SPI Flash ROM
Functional	ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation, Financial Application
Packing	Color Box Dimension■200(W) x 200(D) x 70(H)mm Cases Gross Weight■15.4KGS Cases Net Weight■10.3KGS 20 PCS / Cases, Case size : 720(L) x 410(W) x 200(H)mm
Certificate	CE, FCC, RoHS
Temperature	Operating within 0~60 centigrade **(Suggest to use system FAN)** Storage within -20-85 centigrade
Form Factor	Mini ITX Form Factor(170mmx170mm)

Product Accessories
- COM cable
- Manual
- CD
- 1x SATA cable
- I/O shield
- 1x IDE cable