

198.00 EUR

incl. 19% VAT, plus [shipping](#)



- INTEL® Cedar Trail-D Processor D2500 + NM10 Chipset
- Support 2 \* DDR3 800/1067MHz Single CH up to 4GB
- Support 2 \* Serial ATAI (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- Supports 1 \* Realtek RT8111EVL Gigabit LAN
- Support Watch dog Technology
- Support CPU Smart FAN
- Compliance with ErP standard
- Small size and Easy to use

**Model No:**

**JBC200C9K-2500-B**

**Motherboard Specification**

|                                |                                                                                         |
|--------------------------------|-----------------------------------------------------------------------------------------|
| <b>CPU</b>                     | INTEL® Cedar Trail-D Processor D2500 CPU (1.86GHz)                                      |
| <b>Chipset</b>                 | INTEL®NM10 Express chipset                                                              |
| <b>Memory</b>                  | 2 * DDR3 1067MHz Single CH SO-DIMM up to 4GB                                            |
| <b>LAN</b>                     | 1 * RTL8111EVL PCI-E Gigabit LAN                                                        |
| <b>Audio</b>                   | Realtek ALC662 6-Channel HD Audio                                                       |
| <b>Storage</b>                 | 2 * Serial ATA2 3Gb/s connectors                                                        |
| <b>USB</b>                     | Embedded 8 * USB 2.0/1.1                                                                |
| <b>BIOS</b>                    | AMI 16MB DIP Flash ROM                                                                  |
| <b>Form Factor</b>             | Mini-ITX Form Factor, M/B 170 x 170mm                                                   |
| <b>Barebones Specification</b> |                                                                                         |
| <b>Product size</b>            | 210(W) x 258(D) x 65(H)mm                                                               |
| <b>Specs Exposed</b>           | 1 x Slim ODD Drive Bay and 1 x 2.5" HDD Drive Bay ( <b>Only support SATA 2.5" HDD</b> ) |
| <b>Colors</b>                  | Black Color                                                                             |
| <b>Cooling Fan</b>             | Side: 6cm Fan SLEEVE x 1                                                                |
| <b>Front I/O Port</b>          | 2 x USB(V2.0)<br>1 * Power button and 1 * HDD LED                                       |

---

|                            |                                                                                                                                          |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Rear I/O Port</b>       | 4 * USB 2.0/1.1 ports<br>1 * PS2 KB/MS port<br>1* RJ-45 ports<br>1 * Audio I/O port ( Line-in, MIC and Line-out )<br>1 * VGA & HDMI port |
| <b>Power supply</b>        | 12V DC in                                                                                                                                |
| <b>Standard Accessory</b>  | 1. 60W AC-DC Adapter x1 and Power Cord x1<br>2. Stand x 4 and SATA cable x 1                                                             |
| <b>Functional</b>          | Set Top Box, Thin Client, Car Entertainment, Smart Mini PC, POS/POI, KIOSK                                                               |
| <b>Packing</b>             | Color Box Dimension■417(W) x 137(D) x 296(H)mm<br>Gross Weight■3.65KG<br>Net Weight■3.02KG                                               |
| <b>Certificate</b>         | CE,FCC For Barebones<br>CE,FCC,TUV,UL,CCC,CB For Power Adapter                                                                           |
| <b>Product Accessories</b> | - AC Adapter + power cord<br>- Manual<br>- CD<br>- 1x SATA cable                                                                         |