




999.00 EUR

incl. 19% VAT, plus [shipping](#)

- J4125 Gemini Lake !
- 1x COM !
- Triple Display !
- MiniITX !

- Intel® Gemini Lake J4125 2.0GHz Quad Core MCP Processor (10W, Turbo 2.7GHz)
- 1* DDR4 2400MHz SO-DIMM up to 8GB
- 2* Realtek® RTL8119I GbE, 1* M.2 E-key support WIFI/BT
- 1* SATAIII, 1* M.2 M-key
- 1* HDMI, 1* eDP, 1* LVDS
- 2* RS232/485, 4* RS232, 2* USB3.0, 5* USB2.0
- 12V DC-in
- Thin Mini ITX Form Factor (170 x 170 mm)

Model	– JLI1S-5L
Form Factor	– Mini-ITX (6.7-in * 6.7-in, 170 * 170mm)
Processor System	– Intel® Gemini Lake J4125 2.0GHz/QC Core MCP Processor (10W, Turbo 2.7GHz) – Intel J4125 SoC chipset – AMI 128Mb Flash ROM BIOS
Expansion Slot	– 1* M.2 E-key (2230, support WIFI/BT Module)
Memory	– 1* DDR4 2400MHz SDRAM SO-DIMM up to 8GB
Graphics	– Intel® 600 series Graphics, shared memory – 1* HDMI1.4 (Max Resolution : 3840×2160@24Hz, Co-lay VGA) – 1* LVDS (Max Resolution : 2560×1600@60Hz, Co-lay eDP) – 1* eDP (Max Resolution : 3840×2160@60Hz) – Support Triple Displays
Ethernet	– 2* Realtek® RTL8119I GbE

Audio	– Realtek HD audio – 3W speaker amplifier
Storage	– 1* SATAIII (6Gb/s) – 1* M.2 M-key (2242/2280, SATA or NVMe PCIe2)
Rear I/O	– 1* HDMI – 1* RS232 – 2* RJ45 – 2* USB3.0 – 2* USB2.0 – Line-out/MIC – 12V DC-in
Internal Connector	– 3* USB2.0 – 2* RS232/485 – 2* RS232 – 1* SATAIII – 1* SATA power – 2* M.2 (1* M-key, 1* E-key) – 8bit GPIO (5V) – 1* AT mode – 1* I2C/SMBUS – 1* FP_Audio – 1* speaker – 1* CPU Fan (W/O Smart FAN)
Watchdog Timer	– From Super I/O to drag RESETCON# – 256 segments (10sec ~ 255min)
Power	12V DC-in, AT/ATX Supported – AT: Directly PWR on as Power input ready – ATX: Press Button to PWR on after Power input ready
Compliance	– CE, FCC, RoHS, REACH
Temperature	– Operating: 0°C ~ 60°C – Storage: -20°C ~ 70°C – Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	– Windows 10, Linux